

Product: Polystone® P CubX® White UV

Product characteristics:

- High longitudinal and transversal stiffness
- High chemical resistance
- Light weight, easy handling

Product applications:

- Rectangular tanks for galvanising plant, sewage technology, cleaning systems, purification systems, tank fittings
- Lids and partitions
- Enclosures

	Test method	Unit	Guideline value
<b>Properties for the full cross-ribbed tiwn-wall sheet</b>			
Density	DIN EN ISO 1183	g/cm <sup>3</sup>	0.3
Area weight		kg/m <sup>2</sup>	17.1
Weld strength lattice / covering sheets		MPa	≥ 20
Flatness	DIN EN ISO 15860	mm/m	≤ 3
Water absorption	DIN EN ISO 62	%	< 0.1
<b>Properties for the covering sheets</b>			
Density, RT	DIN EN ISO 1183	g/cm <sup>3</sup>	0.92
Yield stress	DIN EN ISO 527	MPa	24
Elongation at break	DIN EN ISO 527	%	> 50
Tensile modulus of elasticity	DIN EN ISO 527	MPa	1200
Notched impact strength	DIN EN ISO 179	kJ / m <sup>2</sup>	> 30

The data stated above are average values ascertained by statistical tests on a regular basis. They are in accordance with DIN EN 15860. The data above are provided purely for information and shall not be regarded as binding unless expressly agreed in a contract of sale.