



Product Specification **A5068**

Taconic's A5068 is a PTFE coated glass fibre product with a medium PTFE content and silicone adhesive with a corrugated yellow backing liner. Mainly used as a high temperature release material in the packaging, plastics, PVC welding and composite industries as well as a liner in mould release and roller covering applications, A5068 is seen as offering excellent value and superior performance. Standard widths of A5068 include 1000mm & 1500mm as well as slit rolls from 10mm and upwards.

| Product Properties | Units | Value | Tolerance | Test Method |
|---------------------------|----------|----------------------|-----------|-------------|
| Adhesive Type | | SILICONE | | |
| Substrate Type | | E-GLASS | | |
| Total Weight of Substrate | g/m2 | 272 | | ISO 2286-2 |
| % Coating of Substrate | % | 61 | | |
| Substrate Thickness | micron | 128 | | |
| Adhesive Thickness | micron | 60 | | ISO 2286-3 |
| Total Product Thickness | micron | 188 | | |
| Adhesive Strength | N/25,4mm | 12 | Typical | ISO 8510-2 |
| | | 10 | Minimum | |
| Operating Temperature | °Celsius | -73° to +260° | | |

Information contained in this document is based on our general experience and is given in good faith, but we are unable to accept responsibility in respect to factors which are outside our knowledge or control. All data is subject to change without notice.



Please contact us for samples or a quotation

Taconic International Ltd
Ireland
www.taconic-ipd.com
info@taconic-ipd.com



Taconic France
France
www.taconic-ipd.fr
info@taconic-ipd.fr

Taconic International Ltd
Germany
www.taconic.de
info@taconic.de

Wildcat Taconic
United Kingdom
www.taconic-ipd.com
info@wildcat-taconic.com

Taconic SP z.o.o
Poland
www.taconic-ipd.pl
biuro@4taconic.com



For queries in North America please visit www.4taconic.com or email info@4taconic.com

